

## Installing DP Plus Twin with Super Buddy™ meter



**Connections:** Connect the Super Buddy to the DP Plus head.

### Meter Setup:

Push the **SYST** System soft-key to select the following:

- REGION                    your geographic region
- SERVICE                 **Dish Network**
- SYSTEM                 **Dish Pro Plus**
- LNB MODEL             **DP Plus/Twin**
- SWITCH TYPE         defaults to **DPP Twin**

To make selections, arrow to the entry to change and press **Enter**, then arrow to the desired option and press **Enter**. Press **EXIT** or **DONE** to return to Run Mode.

### Run Mode:

Press the **LNB** soft-key to power the LNB and select the satellite. The orbital slot is displayed in upper left corner.

LNB 1 = 119°

LNB 2 = 110°

NOTE: For multi-LNB systems we recommend you use the **LNB** button to select different satellites rather than the left/right arrows.

After pressing the **LNB** soft-key to power the LNB and select the 119° satellite:

- Align the antenna to obtain a strong signal level and **LOCK**.
- Press the **ID** soft key to verify the satellite. "ID VERIFIED" means you are pointed correctly.
- If ID fails, press **SCAN** soft-key and Super Buddy will find the satellite you are aimed at.

Once you have the dish peaked at 119:

- Press the **LNB** button again to select the 110 LNB and satellite
- Verify that a strong signal is present, adjust the skew or re-peak if needed
- Press the **ID** button to verify it is the correct satellite



## Application Note

10/27/2006

Applied Instruments, Inc. • 5230 Elmwood Ave. • Indianapolis, IN USA 46203 • T (317) 782-4331 • [www.appliedin.com](http://www.appliedin.com)